

# TYPAR® FLEXIBLE FLASHING TYPICAL CHARACTERISTICS

FOR COMMERCIAL AND RESIDENTIAL APPLICATIONS

Characteristic	Test Method	Value
Adhesive		Butyl Rubber Copolymer
Recommended UV Exposure Limit		180 Days
Low Temperature Flexibility	ASTM D-1970	PASS
Nail Sealability	ASTM D-1970	PASS
Tensile Strength	ASTM D-5034	PASS

ROLL SIZES:	<b>6" x 75'</b>
	Rolls/Case: 3
	<b>9" x 75'</b>
	Rolls/Case: 2

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, **WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, OTHER THAN THOSE WARRANTIES DESCRIBED IN THE TYPAR® WEATHER PROTECTION SYSTEM LIMITED WARRANTY LOCATED ONLINE AT [HTTP://WWW.TYPAR.COM/ DOWNLOADS](http://www.typar.com/downloads), SUBJECT TO THE LIMITATIONS AND EXCLUSIONS DESCRIBED THEREIN.**

Made in USA of U.S. and Global Components. © 2017, Berry Plastics Corporation.  
TYPAR® is a registered trademark of Berry Plastics Corporation or its affiliate.  
Please visit [TYPAR.com](http://TYPAR.com) for installation instructions and warranty information.  
Building Wraps | Flashings | Construction Tape | Fasteners



3392

