

TYPAR® Construction Tape Three Part Specs:

SPECIFICATIONS:

PART I – GENERAL

- 1.1 Section Includes
 - A. Tymar Construction Top
 - B. Primers.
 - C. Fasteners.
- 1.2 References
 - A. ASTM International
 - 1. ASTM D-903, Standard Test Method for Peel or Stripping Strength of adhesive bonds.
 - 2. ASTM D-2533, Standard practice for Twisting Load-Strain Properties.
 - 3. ASTM D-1970, Standard Specification for Self-Adhesion polymer modified bituminous sheet materials.
- 1.3 Submittals:
 - A. Product Data: Submit manufacturer current technical literature for each type of product.
 - B. Submit copies of test results showing performance characteristics equaling or exceeding those specified.
- 1.4 Quality Assurance
 - A. Qualifications
 - 1. Installer shall have documented successful experience with installation of TYPAR Flashing products.
 - 2. Installation shall be in accordance with manufacturer's installation guidelines and recommendations.

PART 2 - PRODUCTS

- 2.1 Manufacturer
 - A. Berry Global, Inc., 70 Old Hickory Blvd, Old Hickory, TN 37138; 800-284-2780; www. TYPAR.com
- 2.2 Materials
 - A. Tymar Construction Tape
 - 1. Description
 - a. Face material composition: polyethylene barrier
 - b. Face color: Gray
 - c. Adhesive composition: Acrylic
 - d. Thickness: 3.6mil
 - e. Dimensions: 1-7/8" x 165', 3" x 165'
 - B. Performance characterizations
 - 1. Temperature Resistance: 0°F (-18°C) – Min. application temperature
230°F (110°C) – Max. application temperature
 - 2. Peel Adhesion PSTC-1*
 - 3. Tensile strength PSTC – 31*
- 2.3 Accessories
 - A. Primer: Use 3M™ Super77™ or equal
 - B. Flashing Tape: Tymar All-Temperature Flashing, Tymar Flexible Flashing, and Tymar Butyl Flashing
 - C. Fastener: Fastener is dependent on substrate construction
 - D. Sealant: Must comply with ASTM C920 elastomeric polymer sealant

PART 3 – EXECUTION

- 3.1 Examination
 - A. Verify substrate and surface conditions are in accordance with the flashing manufacturer's recommendation.
- 3.2 Installation
 - A. Follow the TYPAR flashing installation procedures
- 3.3 Protection
 - A. Protect installed self-adhesive and flashing tapes from damage during construction



MADE IN USA. ICC #ESR-1404 • CCMC #12884-R • CCMC #12892-R
Tymar is a registered trademark of Berry Global, Inc. and any of its affiliates ©2019
Please visit tymar.com for installation instructions and warranty information
Berry Global, Inc. 70 Old Hickory Blvd., Old Hickory, TN 37138 USA, tymar.com