

TYPAR® CONSTRUCTION TAPE

CCMC-APPROVED (#14190-R)

TYPICAL CHARACTERISTICS

FOR RESIDENTIAL, MULTI-FAMILY AND COMMERCIAL APPLICATIONS

| Characteristic | Test Method | Value |
|------------------------|-------------|--|
| Peel Adhesion | PSTC-101* | Immediate TYPAR®: 25 oz/in Stainless steel: 50 oz/in |
| Tensile Strength | ASTM D1000 | 34 lbs/in |
| Total Thickness | ASTM D1000 | 3 mils |
| Temperature Resistance | | 14°F (-10°C) – Min. application temperature 180°F (82°C) – Max. application temperature |

*Pressure-Sensitive Tape Council.

ROLL SIZE:

63.5 mm x 55 M (2.5" x 180')

Rolls/Case: 20

TYPAR Construction Tape is part of the TYPAR® Lifetime Limited System Warranty when used with the complete TYPAR® Weather Protection System. See online warranty for full details.

The information contained herein is to the best of our knowledge accurate and reliable and is provided for the user's assessment and verification. However, since the circumstances and conditions under which such information and the products discussed can be used may vary and are beyond our control, **we make no warranty, expressed or implied, other than those warranties described in the TYPAR Weather Protection System Limited Warranty located online at [TYPAR.com/downloads](https://www.typar.com/downloads), subject to the limitations and exclusions described therein.**



September 2022 | Made in USA of U.S. and Global Components.
TYPAR® is a registered trademark of Berry Global, Inc. or one of its affiliates.
Please visit [TYPAR.com](https://www.typar.com) for installation instructions and warranty information. CCMC #14190-R.
Building Wraps | Flashings | Construction Tape



3395

