

# TYPAR® CLEAR ACRYLIC FLASHING

## THREE-PART SPECIFICATIONS

### PART 1. GENERAL

#### 1.1 Section Includes

- A. Self-adhering Flashing: **TYPAR Clear Acrylic Flashing**
- B. Primers
- C. Fasteners

#### 1.2 References

- A. ASTM International
  - 1. ASTM D3330/D3330M-04 Standard test method for peel adhesion of pressure-sensitive tape
  - 2. ASTM C765-97 Standard test method for low-temperature flexibility of preformed tape sealants
  - 3. ASTM D1970/D1970M-21 Standard specification for self-adhering polymer modified bituminous sheet materials
  - 4. ASTM D3759/D3759M-05 Standard test method for breaking strength and elongation of pressure sensitive tape
- B. AAMA
  - 1. 711-22 Specification for self-adhering flashing used for installation of exterior wall fenestration products

#### 1.3 Submittals

- A. Product Data: Submit manufacturer's current technical literature for each type of product
- B. Submit copies of test results showing performance characteristics equaling or exceeding those specified

#### 1.4 Quality Assurance

- A. Qualifications
  - 1. Installer shall have documented successful experience with installation of TYPAR Flashing products
  - 2. Installation shall be in accordance with manufacturer's installation guidelines and recommendations

### PART 2. PRODUCTS

#### 2.1 Manufacturer

- A. FIBERWEB-TYPAR®, 70 Old Hickory Blvd, Old Hickory, TN 37138; +1 615-847-7000; www.TYPAR.com.

#### 2.2 Materials

- A. Self-adhering Flashing
  - 1. Description: **TYPAR Clear Acrylic Flashing**
    - a. Face Material Composition: **Polypropylene film**
    - b. Face Color: **Clear film**
    - c. Adhesive Composition: **Acrylic adhesive**
    - d. Thickness: **16.0 mil**
    - v. Release Liner: **Clear backsplitted PET film**
    - e. Dimensions: 4" x 75', 6" x 75', 9" x 75', 12" x 75'
- B. Performance Characteristics
  - 1. Nail sealability ASTM D1970-21 PASS
  - 2. Low temp pliability ASTM C765-91 PASS
  - 3. Tensile strength ASTM D3759-05 PASS
  - 4. Peel adhesion ASTM D3330-04 PASS

#### 2.3 Accessories

- A. Primer: Use 3M™ Super77™ or equivalent product
- B. Seam tape: TYPAR® Construction Tape
- C. Fastener: Fastener is dependent on substrate construction
- D. Sealant: Must comply with ASTM C920. TYPAR® HD Heavy-Duty Sealant

### PART 3. EXECUTION

#### 3.1 Examination

- A. Verify substrate and surface conditions are in accordance with the flashing manufacturer's recommendation.

NOTE - Flashing manufacturer recommends weather barrier be installed prior to the installation of the windows

#### 3.2 Installation

- A. Follow the TYPAR® flashing installation procedures

#### 3.3 Protection

- A. Protect installed flashing from damage during construction



1185\_0924

Made in USA. © 2024.  
Please visit [TYPAR.com](http://TYPAR.com) for installation instructions and warranty information.  
Building Wraps | Flashings | Construction Tape | Sealant

